

SEMI-AUTOMATIC WAT CASE SEALER



KN-2626U

Box Hold-Down Table



The Kingnode **KN-2626U** semi-automatic case sealer is specially designed for sealing boxes with water-activated tape. It can quickly complete both the top and bottom sealing actions in one go, significantly improving the efficiency of the sealing process. Its advanced design concept integrates safety, efficiency, convenience, and eco-friendliness, aiming to provide you with a unique user experience.

FEATURES

- Accommodates tape rolls with a maximum diameter of 500 mm, reducing the frequency of tape changes.
- Tape dispensing units on the top and bottom for easy tape replacement.
- Holds tape rolls with core diameters of 1.5" and 3".
- Adjustable tape dispensing units to fit tape widths from 50 mm to 76 mm.
- Side belt drive mechanism holds the box between two conveyor belts to ensure carton stability.
- Manual adjustment for carton height and width, making operation simple.
- Easy-to-use water refill system.
- Touch control interface for convenient setting of tape length and other parameters; tracks the number of sealed boxes.
- Heavy-duty casters with adjustable legs to achieve optimal matching and improve efficiency.
- Easily removable infeed and outfeed tables for convenient case sealing operations.
- Seals 8-13 cartons per minute, depending on carton size.
- Operation mode: top and bottom center seal.

SPECIFICATIONS

PRODUCT	KN-2626U SEMI-AUTOMATIC WAT CASE SEALER
Min Case (L x W x H)	5.9" × 5.9" × 6.7" (150 mm × 150 mm × 170 mm)
Max Case (L x W x H)	Inf × 26" × 26" (Inf × 660 mm × 660 mm)
Case Weight	max. 132 lbs (60 kg)
Belt Speed	72 ft/min (22 m/min)
Electric/Pneumatic	110 V, 60 Hz, 10 A, Single Phase or 220 V, 50/60 Hz, 5 A, Single Phase
Tape Width	2" - 3" (50 mm - 76 mm)
Conveyor Height	28" - 32" (710 mm - 820 mm)
Machine Weight	970 lbs (440 kg)
Machine Dimension	128" × 53" × 70" (3260 mm × 1350 mm × 1790 mm)

